



户内 单相 环氧树脂浇注式

INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

- 产品性能符合标准 GB1208和IEC60044-1
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 额定绝缘水平 40.5/95/185kV
Rated insulation level 40.5/95/185kV
- 额定二次电流: 5A或1A
Rated secondary current 5A or 1A
- 额定频率50Hz或60Hz
Rated frequency 50Hz or 60Hz
- 环境温度: -5℃~+40℃
Ambient temperature -5℃~+40℃



单变比 single transformation ratio

额定一次电流 Rated primary current(A)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)					一秒热稳定电流 1s thermal current (kA)	动稳定电流 Rated dynamic current (kA)
		0.2	0.5	10P10	10P15	5P20		
50-200	0.2/0.2/10P/10P 0.2/0.5/10P/10P 0.2/10P/10P/10P 0.5/10P/10P/10P 10P/10P/10P/10P	20	40	50	40	30	120lin	300lin
300-400							100lin	250lin
500-800							50	100
1000-1250							56	110
1500、1600							75	110

两变比 two transformation ratio

额定一次电流 Rated primary current(A)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)					一秒热稳定电流 1s thermal current (kA)	动稳定电流 Rated dynamic current (kA)						
		0.2	0.5	10P10	10P15	10P20								
50-100	0.2/0.2/10P/10P 0.2/0.5/10P/10P 0.2/10P/10P/10P 0.5/10P/10P/10P 10P/10P/10P/10P	15	25	50	40	30	120lin	300lin						
75-150									16	40				
100-200											20	50		
150-300							31.5	80						
200-400													40	100
300-600														
400-800														
500-1000														
600-1200							20	40						
750-1500									50	100				
800-1600														

三变比 three transformation ratio

额定一次电流 Rated primary current(A)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)					一秒热稳定电流 1s thermal current (kA)	动稳定电流 Rated dynamic current (kA)						
		0.2	0.5	10P10	10P15	10P20								
50-75-100	0.2/0.2/10P/10P 0.2/0.5/10P/10P 0.2/10P/10P/10P 0.5/10P/10P/10P 10P/10P/10P/10P	15	25	50	40	30	120lin	300lin						
75-100-150									16	40				
100-150-200											20	50		
150-200-300							31.5	80						
200-300-400													40	100
300-400-600														
400-500-600														
500-600-800														
600-800-1000							20	40						
800-1000-1200									50	100				
1000-1200-1500														



外形及安装尺寸 Overall dimension drawing

全封闭 fully encapsulated

